


T1 Over IP for Voice and Data



T1 Circuit Extension Over IP

- ROI Measured in Weeks
- Exploits Efficiency of IP/Ethernet
- Supports Legacy Switches/PBX
- Straightforward Configuration

T1 Voice and Data Over IP

The **IP•Tube DLT1** encapsulates full and fractional T1 circuits into IP packets. T1 Over IP connections provide for the interconnection of PBXs and Telecom Switches via LANs, WANs, MANs, Satellite and Wireless Ethernet.


Transparent Interconnect

The **IP•Tube DLT1's** transparent operation maintains the proprietary signaling required to support PBX features such as call conferences, call forwarding, caller ID and SS7. Legacy phone equipment investment is preserved.

Signaling Support

PRI ISDN, SS7, ESF, D4, SLC-96, Proprietary out of band, and robbed bit signaling is supported. Transparent support for Data, Modem or Fax. Voice quality is not compromised.

The **IP•Tube DLT1** ships with two T1 interfaces with either 1 or 2 active and two 10/100 BaseT Ethernet Interfaces. The T1 interfaces have configurations that provide for independent protocol, compression, packet sizing, buffering, clocking, framing, coding and channel settings. The inactive T1 Port can be activated via a software-based license key for a pay as you grow option.



T1 PRIVATE LINE SERVICES OVER IP

Multi-Site Enterprises, Cellular Service Providers, Education Districts, Universities, National, State and Local Government, and Municipalities incur significant recurring monthly costs for rigid-bandwidth leased lines used only for the interconnection of PBXs and Telecom switches.

The **IP•Tube DLT1** provides organizations with the ability to interconnect their existing phone systems over flexible bandwidth lines that are used to carry data, voice, and video. The Voice Only Leased Line Toll charges assessed by long distance and local carriers are eliminated or dramatically reduced by transporting voice traffic across:

LANs

The most compelling option for the interconnection of T1 based systems is when it can be accomplished over a Local Area Network. The deployment of Fiber based LANS such Gigabit Ethernet, provides organizations with high performance and high quality bandwidth that is especially well suited for the interconnection of PBXs and Switches.

WANs


Wide Area Networks that have sufficient bandwidth and Quality of Service provisioning result in very significant cost savings especially for Multinational Corporations. The **IP•Tube DLT1-C** with lossless data compression, detects idle and redundant data within each voice circuit resulting in a 56 to 1 bandwidth savings.

CELLULAR BASE STATION BACKHAUL

IP Cellular Backhaul

IP•Tube DLT1s provide transparent interconnection of Base Stations, Base Station Controllers and Mobile Switching Centers over IP Ethernet packet-switched networks.

Cellular service providers save substantially by converting to a packet switch network. The Lossless Data compression option, which is especially well suited to Cellular communication links, minimizes the bandwidth required to interconnect.



T1 Over Broadband Networks

Broadband Service Providers

Provide IP Ethernet access networks that generate revenue by transporting T1 leased lines.

Metropolitan Area Networks

Carriers are refocusing investment on the access portion of their network. Ethernet is the access protocol of choice.

MSO Cable Operators

Cable operators connect traditional T1 leased line services over their hybrid fiber coax (HFC) cable networks. MSOs are deploying Gigabit Ethernet backbone based service offerings

Utilities

Utilities generate new revenue by offering traditional T1 leased line over their fiber or power line networks. The IPTube's Assured Delivery Protocol makes it possible to reliably connect Cellular Base Stations over Broadband over Power Lines.

Competitive Local Exchange Carriers

Competitive Local Exchange Carriers are able to offer a very economical alternative by back hauling a customer's phone systems over their Broadband connection.


T1 Over Wireless Ethernet

Wireless Ethernet

The IPTube has proven itself around the world as an effective method for using Commercial Off the Shelf Wireless Ethernet Bridges to interconnect T1 circuits with a return on investment that is measured in weeks.

Interconnection of T1 based data communication systems over wireless as a primary or back up connection is a major application.

The IPTube's Assured Delivery Protocol has the sophistication required for solid performance across a wide range of wireless connections.



IP•Tube DLT1 Standard Features

Dual LAN Interfaces

All **IP•Tube DLT1** models ship with dual 10/100BaseT Ethernet LAN ports. The dual Ethernet interfaces provide for:

- Management interface on LAN port 2 when LAN port 1 is connected to a VPN tunnel
- Alternator Option for load balanced SDSL interconnects
- Protector Option for Redundant Packet Path connections with Constant or Switch Over Criteria
- Optional LAN1 to LAN2 Bridging with Rate Limiting

Assured Delivery Protocol


In order to assure high quality communications over links with intermittent or noisy performance, such as Wireless or Broadband over Power Line, the **IP•Tube DLT1** employs Engage's robust Assured Delivery Protocol with the following benefits:

- Packet out of sequence detection and re-sequencing
- Duplicate skipping,
- Lost packet retransmission with configured delay.

IP•Tube DLT1 Optional Features

DSO Timeslot Multiplexor OPTION - MUX


The **IP•Tube DLT1-MUX** maps DSOs from a central site to as many as 24 remote locations via an IP/Ethernet connection. Get maximum use of expensive DS1 interfaces on PBX, Channel equipment and datacom gear. Also provides Virtual DACS Over IP capability. Mesh DSOs one-to-many or many-to-many.



T1 Switch OPTION -SWT

The T1 switch option enables the T1 Port 1 interface to be manually switched between a T1 circuit connected to T1 Port 2 or to T1 Over IP packets connected with the remote IP•Tube.


- Remote Control of T1 Connection to Telco or T1overIP
- Installation performed by a single Technician
- Quick reversion to Telco during debug of T1overIP



T1 Link Protector OPTION -LPT

The T1 Link Protector provides an automatic backup for T1 circuits with T1 Over IP connecting via Wireless Ethernet, Gigabit Ethernet, IP Satellite Services, xDSL,...

- Automatic Protection Switch for T1 Circuit
- Deliver on Stringent Service Level Agreements
- Back Up for Mission Critical Connectivity
- Disaster Recovery for Public Safety Networks




Lossless Data Compression OPTION -C

The **IP•Tube DLT1-C** continuously detects idle and redundant data within each T1 Voice circuit resulting in as much as a 56 to 1 bandwidth savings. TDM over IP WAN bandwidth is not consumed by silent or redundant samples.

Protector OPTION -PRO

The protector option utilizes the second LAN interface as a redundant path for the interconnection of the IP encapsulated T1 data. The extension of the T1 circuit has a fault tolerant link that is configured to always on, or with switch over criteria.



Alternator Load Balancing OPTION -ALT

The **IP•Tube DLT1-ALT** Alternator option alternatively sends the IP packetized T1 frames on LAN 1 and LAN 2. The Alternator option enables fractional and full T1 circuits to be split over two IP WAN connections such as SDSL.

Rate Limiter OPTION -RLM

The **IP•Tube DLT1-RLM** Rate Limiter option limits the WAN bandwidth utilized by the LAN1 to LAN2 bridge. Rate Limiting the traffic enables the reservation of the WAN bandwidth for time the sensitive T1 Over IP real time connections. Great for Wireless WAN T1 applications.



Rate Governing is only applied in the direction to the WAN to minimize latency. The data rate governor utilizes Time Division Multiplexing based clocking to provide for Nx64, NxT1 and NxFT3 bandwidth regulation that is configured from 64 kilobits up to 45Mbps.

Pay-As-You-Grow Field Upgrades

The **IP•Tube DLT1s** is designed for Pay-As-You-Grow expansion. Customers can elect to economize initial installation by purchasing a single active T1 port, and then enable the additional T1 port via a software-based license key. Field Upgrade benefits are extended to Loss less Data Compression, Protector, and Alternator.

Technical Specifications

LAN Network Interface:

- Two 10/100BaseT Full/Half Ethernet
- Auto negotiation or Configured Speed and Duplex

LAN Network Protocols Supported:

- IP, TCP, UDP, ICMP
- Assured Delivery Protocol
- DHCP • DNS Address Discovery • Dynamic DNS

1 to 4 Duplicate Packet Transmission:

- Resilient performance through a lossy interconnect.

T1/Fractional T1 Specifications:

- One or two Port Models • Connects directly to T1 or DS1
- Framing - ESF or D4 • Coding - B8ZS or AMI
- Supports DS0 assignments from 1 to 24
- Not Contiguous Configuration x-y,z Supported

T1 Over IP Protocol:

- TDM Over IP
- Circuit Extension Services Over IP - CESOIP
- HDLC Over IP - HDLCOIP
- Frames Per Packet Configured 8 to 56
- Low Latency Mode: 1 millisecond 8 T1 frames
- Max Payload Mode: 7 millisecond 56 T1 frames
- Comprehensive Clocking: Internal, Network, Adaptive

TFTP Online Upgrade Capable (FLASH ROMs)

- IPTube is fully operational during upgrade



Lossless Data Compression Option:

- Detects idle and redundant data within each DS0
- Configured Silence Detection Range
- Interconnect bandwidth is not consumed by silent or redundant data
- Low Latency 8 to 1 Compression settings from 8 to 1 to 56 to 1

Quality of Service Support:

- IP Type of Service (TOS) CLI configured • IANA Registered UDP Port 3175
- 802.1p/q mac level prioritization

Regulatory:

- CE • Safety -IEC60950 • EMC - CFR 47 Part 15 Sub Part B:2002, EN55022:1994+A1&A2, EN55024, ICES-003 1997, CISPR 22 Level A
- Telecom Part 68

Management:

- Telnet support with Edit and Paste Template Files
- Console Port for Out of Band Management
- SNMP support (MIB I, MIB II) with configured traps
- Remote config., monitoring, & reset
- Telco Diagnostics: Local Loop, Remote Loop

Rear Panel/Power:

- 10-30 VDC, 1.0A. • Screw Locking Connector
- Universal Adapter 100/240 VAC 50/60 Hz
- Optional -48V 0.25 Amp • Hot Standby
- Dimensions: 9" (L) x 7.3" (W) x 1.50" (H)

How to Order – IP•Tube DLT1

Part No.	Description	Notes
220-1544-0x	IP•Tube DLT1, xT1 (x=1 - 2 Ports)	Base Model Specify # of T1 Ports Enabled
222-1544-Cx	IP•Tube DLT1 with xT1 Compression	w/Lossless Data Compression Option
Base Options		Specify as suffix
-ROHS	ROHS compliant materials and processes	Restriction of Hazardous Substances no PB
-MUX	T1 Multiplexor and DACS	Groom 2 to 24 remote locations Over IP
-SWT	T1 Switch Option	Provides for Manual Switching of T1-T1OverIP
-LPT	Link Protector Option	Automatic T1 Circuit Backup with T1OverIP
-PRO	Protector Option	Fault Tolerant Network Interconnect
-ALT	Alternator Load Balancing Option	Load Balancing Inverse Mux
-RLM	Rate Limiter Option	Reserve T1 Over IP Bandwidth
Power Options		Specify as suffix
-DCMOD	Power Module 10/30 VDC ADAPTER	Ships with Universal Adapter 100/240 50/60
-WIRED	Power Supply Module 10/30 VDC Screw Term	
-N48VDC	Power Supply Module Negative 48 Volt DC	Isolated Negative 48 Volt Power
Rack Mount Option		Specify as suffix
-RACKMNT	19/23" Wide Rack Mount Brackets	Enclosure Nut Serts Installed